



## Комплексное решение для багетных мастерских

### SHH-3H

#### SPECIFICATIONS:

<b>Base Material:</b>	100%polyester
<b>Surface Finish:</b>	waterbased glossy
<b>Weight(g/m2):</b>	200±5 gsm
<b>Width:</b>	24"/36"/42"/44"/50"/60"/72"
<b>Length:</b>	18m/30m/50 or Customized
<b>Core:</b>	2"/3"

#### PRODUCT FEATURES

Superior tear resistance  
Bright white Matte surface  
Applied without wrinkles  
Perfect color control  
Clear texture

#### APPLICATION:

Office printing, artistic giclee prints, advertising, exhibition layout, home decoration.

#### COMPATIBILITY INK AND PRINTER:

<b>Ink:</b>	<b>Printer:</b>
DYE	Most aqueous printing systems
PIGMENT	Especially Hp, Epson, Canon, Rolan, etc
UV	

#### PRODUCT GUIDELINE:

##### Printing Condition

Dry time will vary depending on ink type.  
Suitable printing condition:  
Temperature 15-30°C (59~86(°F))/Humidity 30~60%.

##### Storage

It is recommended to store in the closed original packing in a cool and dry environment.  
Temperature 10~27°C (50~80°F), Relative Humidity 50%RH.  
One year stored in the recommended condition.

#### NOTE

The information described above is our test criteria, All material should be tested by customers to determine the suitable products. Printer or ink change may affect printing results.